

ENDURA EVC-MT19

Motorola APX Series

Rugged In-Vehicle Charger

APX6000 / APX6000XE / APX8000 / APX8000XE
 (available special order for APX7000 / APX7000XE)



EVC-MT19 Specifications

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temp	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Compatible Chemistries	Li-Ion / LiPo / NiMH
Input Voltage (Minimum)	12V / 2.8A for charging device from USB port and radio battery
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-MT19, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.6" x 5.3" x 3.1" / 66.4 x 133.9 x 77.8 mm
Unit Weight	0.60 lbs. / 272 g



Charges all Power Products and OEM batteries, including those with higher end voltage requirements.



PM4486LIPIC

Replaces PN: PMNN4486
 3400 mAh / IP68 rated
 2-year warranty



BP7034PLPU

NON-RECHARGEABLE BATTERY
 FOR EMERGENCY USE
 4500 mAh / Japanese cells



PM4487LIPIC

Replaces PN: PMNN4487
 4900 mAh
 2-year warranty



EC12MV3-MT19T-D

ENDURA 12-UNIT DESKTOP CHARGER
 Shown with optional in-vehicle mounting bracket

EVC-MT19-4

RUGGED 4-UNIT CHARGER

- Low profile and space efficient design
- Horizontal or vertical mounting

