

# Kenwood NX5000 Series

## EC12M-KW4A-D\*

FOR KENWOOD NX5200 / NX5300 / NX5400 / TK5230 /  
TK5330 / TK5430 / VP5000 Series / VP6000 Series



### SPECIFICATIONS – EC12M-KW4A-D

<b>DIMENSIONS (W X L X H)</b>	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
<b>WEIGHT</b>	1.63 kg / 3.6 lbs (charger only)
<b>COMPATIBLE CHEMISTRIES</b>	Li-Ion / LiPo / NiMH / NiCd
<b>CHARGER INPUT</b>	12-24V DC / 10.0A (minimum)
<b>CHARGE RATE</b>	800 mA (10.6V – 13.5V)
<b>APPROVALS</b>	FCC <sup>A</sup> / BC <sup>B</sup> / DOE <sup>C</sup> / CE

Specifications subject to change without notice.  
(A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



Intrinsically Safe

#### LEKNBL2LIIS

3400 mAh / Li-Ion

*Same capacity as KNB-L3M, but thinner*

1-year Warranty



#### BPKNBL2LI-34

3400 mAh / Li-Ion

*Same capacity as KNB-L3M, but thinner*

1-year Warranty



#### BPKNBL2LI-26

2600 mAh / Li-Ion

Replaces KNB-L1M and KNB-L2M

1-year Warranty



#### ESM-28-KW2

Speaker Mic

IP67 Rated

*Extra Loud Audio*

3-year Warranty



#### EC1M-KW4A

Single Unit Charger  
with Replaceable  
Charging Pod  
2-year Warranty

*\*Also Charges: NX200S, NX210, NX210G, NX300, NX300S, NX410, NX411, NX5300, NX5400, TK3180, TK5210, TK5210G, TK5220, TK5230, TK5310, TK5310G, TK5320, TK5330, TK5410, TK5430, VP5230, VP5330, VP5430, VP6230, VP6330, VP6430. Compatible with KNB-41NC / KNB-73LCM (IS batteries). Not compatible with KNB-50NC / KNB-72LC / KNB-L5S (IS batteries).*

### EC12M-KW4A-D FEATURES

- Properly charges Kenwood KNB-L1M/L2M/L3M batteries.
- Provides cold and hot battery monitoring for batteries with temperature sensing circuitry.
- Includes AC to DC power supply and six dual position charging pods. Single, dual and 6-unit models also available.
- Additional accessories available for in-vehicle use.