



# EC12M-MT13-D

## Motorola XTS Series Twelve-Unit Charger

FOR MOTOROLA MT1500 / PR1500 / XTS1500  
XTS2500 / XTS3000 / XTS3500 / XTS5000



### SPECIFICATIONS – EC12M-MT13-D

<b>DIMENSIONS (W X L X H)</b>	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
<b>WEIGHT</b>	1.63 kg / 3.6 lbs (charger only)
<b>COMPATIBLE CHEMISTRIES</b>	Li-Ion / LiPo / NiMH / NiCd
<b>CHARGER INPUT</b>	12-24V DC / 10.0A (minimum)
<b>CHARGE RATE</b>	800 mA (10.6V – 13.5V)
<b>APPROVALS</b>	FCC <sup>A</sup> / BC <sup>B</sup> / DOE <sup>C</sup> / CE

Specifications subject to change without notice.

(A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



#### PM9858LIPIC

4100 mAh / LiPo

Fits: XTS1500 / XTS2500 /  
MT1500 / PR1500\*

**2-year Warranty**



#### BP9858MHIC

2500 mAh / NiMH

Fits: XTS1500 / XTS2500 /  
MT1500 / PR1500\*

**1-year Warranty**



#### BP6034LIIC

4400 mAh / Li-Ion

Fits: XTS3000 /  
XTS3500 / XTS5000\*

**1-year Warranty**



#### PM8299LIPXT

4600 mAh / LiPo

Fits: XTS3000 /  
XTS3500 / XTS5000\*

**2-year Warranty**



#### BP8299MHUC

3800 mAh / NiMH

Fits: XTS3000 /  
XTS3500 / XTS5000\*

**1-year Warranty**

\*Additional battery models for XTS radios available, including non-rechargeable primary lithium batteries for emergency use.

### EC12M-MT13-D FEATURES

- Properly charges all OEM batteries.
- Provides cold and hot battery monitoring for batteries with temperature sensing circuitry.
- Includes AC to DC power supply and six dual position charging pods. Single, dual and 6-unit models also available.
- Additional accessories available for in-vehicle use.