



EC12M-MT13-D

Motorola XTS Series

Twelve-Unit Charger

FOR MOTOROLA MT1500 / PR1500 / XTS1500
XTS2500 / XTS3000 / XTS3500 / XTS5000



SPECIFICATIONS – EC12M-MT13-D

DIMENSIONS (W X L X H)	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
WEIGHT	1.63 kg / 3.6 lbs (charger only)
COMPATIBLE CHEMISTRIES	Li-Ion / LiPo / NiMH / NiCd
CHARGER INPUT	12-24V DC / 10.0A (minimum)
CHARGE RATE	800 mA (10.6V – 13.5V)
APPROVALS	FCC ^A / BC ^B / DOE ^C / CE

Specifications subject to change without notice.

(A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



SMART
Battery

PM9858LIPIC

4100 mAh / LiPo

Fits: XTS1500 / XTS2500 /
MT1500 / PR1500*

2-year Warranty



SMART
Battery

BP9858MHIC

2500 mAh / NiMH

Fits: XTS1500 / XTS2500 /
MT1500 / PR1500*

1-year Warranty



SMART
Battery

BP6034LIIC

4400 mAh / Li-Ion

Fits: XTS3000 /
XTS3500 / XTS5000*

1-year Warranty



PM8299LIPXT

4600 mAh / LiPo

Fits: XTS3000 /
XTS3500 / XTS5000*

2-year Warranty



BP8299MHUC

3800 mAh / NiMH

Fits: XTS3000 /
XTS3500 / XTS5000*

1-year Warranty

*Additional battery models for XTS radios available, including non-rechargeable primary lithium batteries for emergency use.

EC12M-MT13-D FEATURES

- Properly charges all OEM batteries.
- Provides cold and hot battery monitoring for batteries with temperature sensing circuitry.
- Includes AC to DC power supply and six dual position charging pods. Single, dual and 6-unit models also available.
- Additional accessories available for in-vehicle use.