

# EC12M-MT16A-D

# **Motorola XPR 7000 Series**

Twelve-Unit Charger

FOR MOTOROLA XPR7350 | XPR7380 | XPR7550 | XPR7580



#### SPECIFICATIONS - EC12M-MT16A-D

DIMENSIONS (W X L X H)	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
WEIGHT	1.63 kg / 3.6 lbs (charger only)
COMPATIBLE CHEMISTRIES	Li-lon / LiPo / NiMH / NiCd
CHARGER INPUT	12-24V DC / 10.0A (minimum)
CHARGE RATE	800 mA (10.6V – 13.5V)
APPROVALS	FCC <sup>A</sup> /BC <sup>B</sup> /DOE <sup>C</sup> /CE

Specifications subject to change without notice. (A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



### ESK-1WATD-MT9

Surveillance Kit w/ **Quick Disconnect** Also Fits: XPR6100 | XPR6500 3-year Warranty



#### BP4409LIIC

2500 mAh | 18.5 Wh Li-Ion | IP67 Rated Also Fits: APX4000 | XPR3300 1-year Warranty



### BP4406LIIC

2000 mAh | 14.4 Wh Li-lon | IP68 Rated Also Fits: DP4800 | XPR3300 1-year Warranty



#### ESM-20-MT9

Speaker Mic w/ Rotating Clip Also Fits: XPR6100 | XPR6500 3-year Warranty



## EC1M-MT16B

Single-Unit Vehicle Charger Charges: NiCd, NiMH, Li-lon, and LiPo batteries 2-year Warranty

## EC12M-MT16A-D **FEATURES**

- Properly charges all OEM batteries.
- Provides cold and hot battery monitoring.
- Includes AC to DC power supply and six dual position charging pods. Single, dual and 6-unit models also available.
- Additional charger accessories available for in-vehicle use.

