ENDURA

EC12M-MT3-D

Motorola CP200 Series

Twelve-Unit Charger

FOR MOTOROLA CP200d | CP250 | EP450 | PR400

SPECIFICATIONS - EC12M-MT3-D

DIMENSIONS (W X L X H)	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
WEIGHT	1.63 kg / 3.6 lbs (charger only)
COMPATIBLE CHEMISTRIES	Li-Ion / LiPo / NiMH / NiCd
••••••••••••	
CHARGER INPUT	12-24V DC / 10.0A (minimum)
CHARGE RATE	800 mA (10.6V – 13.5V)
CHARGE RATE	800 IIIA (10.0V - 13.3V)
APPROVALS	$FCC^{A}/BC^{B}/DOE^{C}/CE$

Specifications subject to change without notice.

(Å) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



BP4497LIXT 2500 mAh / Li-Ion Battery Includes Belt Clip 1-year Warranty



ESK-1WATD-MT1 1 Wire Surveillance Kit Quick Disconnect Audio Tube 3-year Warranty

*Additional battery chemistries for Motorola CP200 radios are available, including NiMH and NiCd.

- Properly charges all OEM batteries.
- Provides cold and hot battery monitoring for batteries with temperature sensing circuitry.
- Includes AC to DC power supply and six dual position charging pods. Single, dual, 6-unitand in-vehicle models also available.
- Additional accessories available for EC12M-MT3-D for in-vehicle use.



Serving the wireless industry since 1994.





ESM-20-MT1

IP54-rated Speaker Mic

Excellent Value / Compact 3-year Warranty

Compact design charges 12 radios or batteries with the same footprint as a 6-unit charger.

BP4497LI

2200 mAh / Li-Ion* Battery

Includes Belt Clip

1-year Warranty

EC12M-MT3-D FEATURES