

BK KNG In-Vehicle Charger

Rugged Single Unit Charger

EVC-BK2



For KNG-P150, KNG-P400, KNG-P500,
KNG-P800, KNG2-P150, KNG2-P400,
KNG2-P500, KNG2-P800 radios



- Tested to 9 g-force and NFPA compliant.
- Radio may stay powered on while charging.
- Includes DC hardwire cable and easy release tie-down strap.
- USB port for charging mobile phones or tablets.
- AMPS pattern with optional dash / floor mounting brackets available.

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temperature	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Input Voltage (Recommended)	14V – 24V / 2.8A (minimum for radio battery + USB) / 1.0A (minimum for radio battery only)
Input Voltage (Minimum)	12V / 2.8A for USB charging and partial charge of radio battery
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-BK2, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.4" x 5.3" x 2.3" / 66.4 x 133.9 x 58.3 mm
Unit Weight	0.53 lbs. / 240 g



LEVCA-M



LEVCA-MHD



Innovative Solutions for Public Safety Professionals



EVC-BK2-4
Rugged 4-unit model also available.