

L3Harris XL-200P In-Vehicle Charger

Rugged Single Unit Charger



EVC-HA3

For L3Harris XL-150P, XL-185P, XL-185Pi, XL-200P, and XL-200Pi radios.



- Tested to 9 g-force and NFPA compliant.
- Radio may stay powered on while charging.
- Includes DC hardwire cable and easy release tie-down strap.
- USB port for charging mobile phones or tablets.
- AMPS pattern with optional dash / floor mounting brackets available.
- Compatible with all L3Harris XL-200P batteries, including IS models 14035-4045-01 / XL-PA4F and 14035-5050-02 / XL-PA4L.

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temperature	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Compatible Chemistries	Li-Ion and LiPo
Input Voltage (Minimum)	12V / 2.8A for charging device from USB port and radio battery
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-HA3, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.6" x 5.3" x 2.3" / 66.4 x 133.9 x 57.7 mm
Unit Weight	0.60 lbs. / 272 g



Rugged 4-unit model also available.