



LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4077LIXT

COMPATIBLE RADIOS	Motorola XPR6100, XPR6300, XPR6350, XPR6380, XPR6500, XPR6550, XPR6580, Vertex Standard VXD720
REPLACES OEM BATTERY	PMNN4065, FNB-V116
COMPATIBLE CHARGERS	Endura TWC1-MT16A, TWC1M-MT16A, TWC2M-MT16-D, TWC6M-MT16A, TWC12M-MT16-D / Logic Energy LEVC-MT16 / Motorola adaptive Impres chargers
VOLTAGE	7.2V
CAPACITY	2500 mAh
CHEMISTRY / CELL TYPE	Li-Ion / Sanyo, Panasonic, or equivalent
BATTERY TYPE	Smart
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	300
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes
THERMAL PROTECTION	Yes
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months
PRODUCT PHOTO	 Dimensions (HxWxD): 5.08" x 2.18" x 0.88" 129.0 x 55.4 x 22.4 mm Weight: 0.37 lbs.