



LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4406LIIC

COMPATIBLE RADIOS	Motorola APX900, APX1000, APX2000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
REPLACES OEM BATTERY	PMNN4406, PMNN4407, PMNN4491
COMPATIBLE CHARGERS	Endura EC1-MT16B, EC1M-MT16B, EC2M-MT16A-D, EC6M-MT16B, EC12M-MT16A-D / Logic LEVCA-MT16 / Motorola IMPRES WPLN4222, PMPN4284
VOLTAGE	7.2V
CAPACITY	2000 mAh / 14.4 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic NCA103450 or equivalent
BATTERY TYPE	Smart
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 10° C to +45° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Smart battery conditions on Motorola IMPRES chargers (conditioning not required for cycle life or battery run time)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CL7144)
WARRANTY	12 months
PRODUCT PHOTO	 Dimensions (HxWxD): 4.51" x 2.18" x 0.71" 114.5 mm x 55.4 mm x 17.9 mm).