



LMR BATTERY SPECIFICATIONS	PART NUMBER
	LE4007MHXTIS

COMPATIBLE RADIOS	Motorola XTS3000, XTS3500, XTS5000, EF Johnson 5100, 51SL ES, Ascend ES
REPLACES OEM BATTERY	RNN4007AR
CERTIFICATIONS & RATINGS	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5 th Edition standard for intrinsically safe use (Class I, II, III, Division 1, Groups C, D, E, F, G, T3C) and non-incendive use (Class I, Division 2, Groups A, B, C, D, T3C). IP64 rated.
COMPATIBLE CHARGERS	Endura EC1-MT13B, EC1M-MT13B, EC6M-MT13B, TWC2M-MT13-D, TWC12M-MT13-D / Logic LEVCA-MT13MH
VOLTAGE / CAPACITY	7.5V / 3500 mAh
CHEMISTRY	NiMH
CELL TYPE	FDK HR-4/3AU (Japanese)
OPERATING TEMPERATURE	0° C to +50° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid or trickle
CONDITIONER COMPATIBLE	Yes
THERMAL PROTECTION	Yes
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months
PRODUCT PHOTO (Brand: Logic Energy)	 The product photo shows a black Logic Energy LE4007MHXTIS NiMH battery. The battery has a clip at the top and three gold-colored terminals at the bottom. Next to the battery is a detailed label with the following information: logic ENERGY logo - PN: LE4007MHXTIS 7.5V / 3500 mAh / 26.3 Wh - NIMH BATTERY - CAUTION: DO NOT REMOVE OR RECHARGE BATTERY IN KNOWN HAZARDOUS AREA. DO NOT DISPOSE OF IN FIRE. - ATTENTION: NE PAS ENLEVER NI RECHARGER CETTE PILE DANS UN ENDROIT DANGEREUX. NE PAS EXPOSER PRÈS DU FEU. - Intrinsically Safe / Intrinsicement sûr For Class I, II, III, Division 1, Groups C, D, E, F, G, T3C - Non-Incendive For Class I, Division 2, Groups A, B, C, D, T3C - MADE IN USA - SN: 12-1E04 - SGS US logo with number 710297